

IN THE CLAIMS:

Please cancel claims 7-9 and 14-19 and amend claims 1-4 and 11 to read as follows:

1. (Currently Amended) A ring binder mechanism for binding the sheets of loose leaves, the mechanism comprising:

a an elongated spring plate that extends longitudinally and, in profile, has a shallow U-shaped configuration and opposite edges which extend substantially toward each other;

two parallel elongate hinge plates supported by said elongated spring plate for pivotal rotating toggle motion relative to the elongated spring plate about a central hinge line, the hinge plates being mounted in parallel and retained by the opposite edges of the spring plate,;

a plurality of rings for elasp clasping said sheets of loose leaves, each of the rings comprising a pair of half ring elements of circular cross-section mounted on said hinge plates, with one half ring element of each pair being attached to one of the hinge plates and the other half ring element of the pair attached to the other hinge plate, with the two half ring elements of each pair in substantial alignment, the pairs of half ring elements, and the pair of

~~half ring elements being attached on said hinge plates and~~
being movable with said hinge plates to toggle between a
~~closed~~ an open position and ~~an opened~~ a closed position via
~~said hinge plates and forming a substantially annular shape~~
when in the closed position;

wherein ~~nesting portions of~~ free ends of ~~said pair of~~
the half ring of each pair elements form a nesting
configuration when in the closed position, the free end of
one half ring element of each pair having a centrally
concave nesting portion with and the free end of the other
half ring element of the pair having a centrally conical
convex surface nesting portion ~~diminishing the cross-section~~
~~of the cylindrical rod of the half ring element to a~~
cylindrical tip, said concave portion and said convex
portion being symmetrical about an axis line of the
~~cylindrical rods of~~ respective ring elements of the pair, so
that when the pair of half ring elements are in the closed
condition, the ~~nesting portions of said pair~~ free ends of
the half ring elements are aligned to each other and form a
surface-engagement so that the convex nesting portion and
the concave nesting portion are nested together tightly.

2. (Currently Amended) A ring binder mechanism
according to claim 1, wherein ~~the nesting portion with a~~

~~centrally convex portion is formed in a free end of one half ring element of said pair of half ring elements, and the nesting portion with a centrally concave portion is formed in a free end of the other engaging half ring element, said convex nesting portion has an annular conical surface, said concave nesting portion has a conical hole that is formed from its external end surface in the free end of one half ring element, a diameter of the conical hole on the external end surface is being smaller than that of the cylindrical rod of the respective half ring element, a cone angle of said conical hole is smaller than that of the annular conical surface of the centrally protruding outwards nesting portion, when the half ring elements are in the closed condition, the connecting portion between the external end surface of the concave nesting portion and the conical hole thereof engages with the annular conical surface of the convex nesting portion, so that the centrally convex nesting portion is nested in the centrally concave nesting portion.~~

3. (Currently Amended) A ring binder mechanism according to claim 1, wherein ~~the nesting portion with a centrally convex portion is formed in a free end of one half ring element of said pair of half ring elements, and the nesting portion with a centrally concave portion is formed~~

~~in a free end of the other engaging half ring element, said convex nesting portion has a protruding portion, the protruding portion is connected to a surface of the cylindrical rod of the half ring element via an annulus internal end surface, a diameter of the protruding portion on the internal end surface is smaller than that of the cylindrical rod of the half ring element, said concave nesting portion has a opening that is formed from its external end surface, a diameter of the opening on the external end surface is smaller than that of the cylindrical rod of the half ring element and slightly larger than that of said protruding portion on its internal end surface, when the half ring elements are in the closed condition, the external end surface of the concave nesting portion and the convex nesting portion in the free end of one half ring element in each respective pair form a surface engagement, so that the convex nesting portion is nested in the concave nesting portion has a substantially conical protruding portion with an outer diameter of a base of the protruding portion being smaller than the diameter of the respective half ring element.~~

4. (Currently Amended) A ring binder mechanism according to claim 3, wherein ~~the protruding portion of said~~

~~convex nesting portion has a conical shape,~~ the opening of said concave nesting portion in the free end of one half ring element of each respective pair has a substantially conical hole that is formed from its external end surface and an internal cylindrical hole that is connected to said conical hole.

5. (Original) A ring binder mechanism according to claim 4, wherein the protruding portion of said convex nesting portion has a shape that consists of a cylindrical tip and an arc-shaped annular conical base portion, the opening of said concave nesting portion has a conical hole that is formed from its external end surface and an internal cylindrical hole that is connected to said conical hole.

6. (Original) A ring binder mechanism according to claim 3, wherein the protruding portion of said convex nesting portion has a cylindrical shape, the opening of said concave nesting portion has a shape of an internal cylindrical hole.

7. - 9. (Canceled).

10. (Original) A ring binder mechanism according to claim 1, wherein two, three, four or more rings are provided in said ring binder mechanism.

11. (Currently Amended) A ring binder mechanism according to claim 1, wherein said rings are made of metal material, ~~and the metal material can be steel.~~

12. (Original) A ring binder mechanism according to claim 1, wherein said rings are made of plastic material.

13. (Original) A ring binder mechanism according to claim 1, wherein said rings are formed integrally with said hinge plates.

14. - 19. (Canceled).